

WHITELINE

AUTOMOTIVE *Flat out*

BFR54Z is an adjustable rear sway bar designed to fit Ford Falcon AU ser1, 2 & 3 sedan IRS WITHOUT factory fitted sway bar. (Refer application catalogue for exact listing.)

General Fitting Instructions;

Fitment is best done with the vehicle on a drive-on hoist with a secondary lift/ jacky.

1. Raise the vehicle of the ground/hoist so that road wheels fully droop.
2. Remove road wheels. For ease of fitment, it may be beneficial to marginally relocate or drop the rear differential. Using a suitable jack supporting the differential housing, remove front and rear differential mounting bolts and lower the assembly down while still inside the cross-member.
3. Fit sway bar into position, feeding it from one side, (finish inside the cross-member). Refer picture for final position.
4. Using factory captive cross-member nuts and supplied bushes (grease inside surface using grease supplied), brackets and bolts, attach the sway bar to the cross-

member. Using suitable bolts, nuts and washers loosely attach the sway bar link. Note that the link is spaced away from the control arm using 3 smaller washers. If applicable, raise and re-fit the differential assembly in the original position. Re-fit road wheels and lower the vehicle.

5. Tighten all mounting hardware to manufacturers specification.

Note: Please drive carefully while you accustom yourself to the changed vehicle.



A.B.N. 93 051 207 535

Whiteline Automotive 1800 040 003

Code: 211

Code: 211

Whiteline Automotive 1800 040 003

A.B.N. 93 051 207 535



4. Using factory captive cross-member nuts and supplied bushes (grease inside surface using grease supplied), brackets and bolts, attach the sway bar to the cross-

position. (finish inside the cross-member). Refer picture for final

3. Fit sway bar into position, feeding it from one side,

inside the cross-member.

mounting bolts and lower the assembly down while still

differential housing, remove front and rear differential

differential. Using a suitable jack supporting the

2. Remove road wheels. For ease of fitment, it may be

beneficial to marginally relocate or drop the rear

wheels fully droop.

1. Raise the vehicle of the ground/hoist so that road

with a secondary lift/ jacky.

Fitment is best done with the vehicle on a drive-on hoist

General Fitting Instructions;

BFR54Z is an adjustable rear sway bar designed to fit

Ford Falcon AU ser1, 2 & 3 sedan IRS WITHOUT

factory fitted sway bar. (Refer application catalogue

for exact listing.)

Note: Please drive carefully while you accustom yourself to the

changed vehicle.

5. Tighten all mounting hardware to manufacturers

specification.

original position. Re-fit road wheels and lower the vehicle.

applicable, raise and re-fit the differential assembly in the

member. Using suitable bolts, nuts and washers loosely

attach the sway bar link. Note that the link is spaced away

from the control arm using 3 smaller washers. If

WHITELINE

AUTOMOTIVE *Flat out*