

Supplementary Fitting Instructions 1K4028

WHITELINE

PO Box 5666, Minto, NSW, 2566 Australia
Ph: 61 2 9603 0111 Fax: 61 2 9820 2500
E-mail: admin@whiteline.com.au
A.B.N. 68 073 002 034

Flat out

Code: Z275

IMPORTANT: Whiteline Group 4 shock/strut kits are designed for race or off-road use but may be used on-road depending on specific vehicle registration regulations in your area. Extreme care must be taken when adjusting ride height to ensure correct operation of the suspension and any adjustments are at the owners own risk. It is recommended that installation and adjustment be carried out by qualified suspension and chassis specialists.

NOTE: Ride Height denotes adjustment range available only. It is NOT a height setting recommendation.

Part No.	Spec (1) C/D/R/Q	Application				Note	Ride height +/- (2)				Spring Rate				Upper mount (3)	
		Make	Model	Year	Chassis		Front		Rear		Front		Rear		Front	Rear
							mm	inch	mm	inch	kg/mm	lbs/in	kg/mm	lbs/in		
1K4028C	C	Nissan	180/240SX88-94	S13		-60	-2.4	-50	-2.0	5.0	280	4.0	224	OEM	OEM	
1K4028D	D	Nissan	180/240SX88-94	S13		-55	-2.2	-45	-1.8	6.0	336	5.5	308	OEM	OEM	
1K4028R	R	Nissan	180/240SX88-94	S13												
1K4028Q	Q	Nissan	180/240SX88-94	S13												

- Footnote:**
- 1- C - Circuit race / D - Drift / R - Race / Q - Quatermile or Drag race
 - 2- Range of ride height change. + = Raise / - = Lowering. Eg. -60 equates to 60 mm lowering
 - 3- If OEM use stock or existing strut top.



Front strut assembly



Rear strut assembly.

Note large alloy top spring seat.

Warning: Please drive carefully while you accustom yourself to the changed vehicle behaviour.