

Supplementary Fitting Instructions 1K4029



IMPORTANT: Whiteline Group 4 shock/strut kits are designed for race or off-road use but may be used on-road depending on specific vehicle registration regulations in your area. Extreme care must be taken when adjusting ride height to ensure correct operation of the suspension and any adjustments are at the owners own risk. It is recommended that installation and adjustment be carried out by qualified suspension and chassis specialists.

NOTE: Ride Height denotes adjustment range available only. It is NOT a height setting recommendation.

Part No.	Spec (1) Application					Ride height +/- (2)				Spring Rate				Upper mount (3)	
	C/D/R/Q	Make	Model	Year	Chassis	Front		Rear		Front		Rear		Front	Rear
						mm	inch	mm	inch	kg/mm	lbs/in	kg/mm	lbs/in		
1K4029C	C	Mitsubishi	Lancer	01-04	EVO VII VIII	< -55	-2.2	< -50	-2.0	5.0	280	4.5	252	AB	B
1K4029D	D	Mitsubishi	Lancer	01-04	EVO VII VIII										
1K4029R	R	Mitsubishi	Lancer	01-04	EVO VII VIII	< -50	-2.0	< -40	-1.6	10.0	560	9.0	504	AB	B
1K4029Q	Q	Mitsubishi	Lancer	01-04	EVO VII VIII										

- Footnote:**
- 1- C - Circuit race / D - Drift / R - Race / Q - Quatermile or Drag race
 - 2- Range of ride height change. < indicates lowering range, or = indicates amount of drop.
 Example: < -60 indicates up to 60 mm lowering
 OR = -45 indicates average drop 45mm +/- 10 mm (non-adj) .
 - 3- OEM - kit supplied without top mounts, use stock or existing strut top.
 AB - kit supplied with adjustable top bearing mount.
 B - kit supplied with non-adjustable bearing top mount

Warning: Please drive carefully while you accustom yourself to the changed vehicle behaviour.