

Supplementary Fitting Instructions 1K4031



IMPORTANT: Whiteline Group 4 shock/strut kits are designed for race or off-road use but may be used on-road depending on specific vehicle registration regulations in your area. Extreme care must be taken when adjusting ride height to ensure correct operation of the suspension and any adjustments are at the owners own risk. It is recommended that installation and adjustment be carried out by qualified suspension and chassis specialists.

Part No. (1)	Application						Ride Height Range (2)				Spring Rate				Upper mount (3)	
							Front		Rear		Front		Rear		Front	Rear
C/D/R/Q	Make	Model	Year	Chassis	Body	mm	inch	mm	inch	kg/mm	lbs/in	kg/mm	lbs/in			
1K4031	Ford	Falcon	03-05	BA	sedan incl XR6 XR8	< 50	2.0	~ 45	1.8	9.5	532	5.0	280	OEM	OEM	

- Footnote:**
- (1) C - Circuit / D - Drift / R - Race / Q - Quatermile or Drag race
 - (2) Range of ride height change. "<" indicates lowering range, or "~" indicates amount of drop
 Example: < -60 indicates up to 60 mm lowering
 OR ~ -45 indicates average drop 45mm +/- 10 mm (non-adj)
 - (3) OEM - use stock strut top
 AB - supplied with adjustable top mount
 B - supplied with non-adjustable top mount

Warning: Please drive carefully while you accustom yourself to the changed vehicle behaviour.