

# Fitting Instructions W0450-size

# WHITELINE

AUTOMOTIVE *Flat out*

PO Box 5666, Minto, NSW, 2566 Australia  
Ph: 61 2 9603 0111 Fax: 61 2 9820 2500  
E-mail: admin@whiteline.com.au  
A.B.N. 68 073 002 034

Code: Z289

## Application:

W0450-size is a universal sway bar lateral movement lock kit. Available in 18, 20, 22, 24, 27, 30 and 32mm diameters.

## Contents:

Kit contains 1 pair of polyurethane stop rings and 1 pair of stainless steel locking clamps.

## Fitting:

Fitment of W0450-size is easiest done with the sway bar off the car, but can also be done with the sway bar already fitted to the car.

1. With the sway bar centrally located, identify a suitable position for the lock kit. This usually is on the inside of the chassis mount bushes.
2. Clean sway bar off any dirt and grease.

*For best results, it is recommended to use Loctite®-480™ or Sikaflex®-255 extra adhesive or similar. Refer to manufacturer's methods of application.*

3. Fit polyurethane bush next to the D-bush
4. Fit metal clamp over the bush.
5. Using a pincer type plier, crimp the metal clamp over the ring bush. "End cutting pliers", multi-grips or large conventional pliers can also be used.

**Warning:** Please drive carefully while you accustom yourself to the changed vehicle behaviour.



**Warning:** Please drive carefully while you accustom yourself to the changed vehicle behaviour.



1. With the sway bar centrally located, identify a suitable position for the lock kit. This usually is on the inside of the chassis mount bushes.
  2. Clean sway bar off any dirt and grease.
- For best results, it is recommended to use Loctite®-480™ or Sikaflex®-255 extra adhesive or similar. Refer to manufacturer's methods of application.*
3. Fit polyurethane bush next to the D-bush
  4. Fit metal clamp over the bush.
  5. Using a pincer type plier, crimp the metal clamp over the ring bush. "End cutting pliers", multi-grips or large conventional pliers can also be used.

Fitment of W0450-size is easiest done with the sway bar off the car, but can also be done with the sway bar already fitted to the car.

**Contents:**  
Kit contains 1 pair of polyurethane stop rings and 1 pair of stainless steel locking clamps.

**Application:**  
W0450-size is a universal sway bar lateral movement lock kit. Available in 18, 20, 22, 24, 27, 30 and 32mm diameters.

Code: Z289

# WHITELINE

AUTOMOTIVE *Flat out*

PO Box 5666, Minto, NSW, 2566 Australia  
Ph: 61 2 9603 0111 Fax: 61 2 9820 2500  
E-mail: admin@whiteline.com.au  
A.B.N. 68 073 002 034

# Fitting Instructions W0450-size