Car Kit - Commodore VT V6 & LS1 V8 Sedan

8/97 to 11/00 including Acclaim, Berlina and Calais. Excluding GMH 308 and stroked V8



13/08/2001 ABN 93 051 207 535 Page 1

					13/06/2001	ADI	1 93 03 1 207 535	Page i	
Kit contents and price details				Commodore VT sedan V6 & LS1 V8					
Pricing valid till 30/6/2002 but subject to change without notice				Handling Pack All KCOM09H	Sports Pack Low KCOM09S	Sports Pack Superlow KCOM09SL	The Works Low KCOM09X	The Works Superlow KCOM09XL	
		Rec. retail excluding fre Fitting and labour estir		\$ 485.00 \$ 250.00 \$ 735.00	\$ 1,145.00 \$ 320.00 \$ 1,465.00	\$ 320.00	\$ 1,539.00 \$ 550.00 \$ 2,089.00	\$ 1,539.00 \$ 550.00 \$ 2,089.00	
Product	Loc.	Description	Qty						
Springs(1)	Front	Low sport rate - 355mm Superlow sport rate - 340mm	1		73520	73518	73520	73518	
	Rear	Low sport rate - 345mm Superlow sport rate - 335mm	1		83051A	83050A	83051A	83050A	
Shocks(5)	Front	Replacement gas sport strut - right	1		120190	120190	120190	120190	
		Replacement gas sport strut - left	1		120200	120200	120200	120200	
	Rear	Replacement mono tube gas sport shock	2		110190	110190	110190	110190	
Bars	Front Rear	Blade adjustable - 30mm Heavy duty fixed - 18mm	1 1	BHF43Z BHR50			BHF43Z BHR50	BHF43Z BHR50	
Align	Front Rear	Camber adjustment Camber toe adjusting kit (6)	1	OE	KCA330	KCA330	OE KCA330	OE KCA330	
Other	Front	Upper adjustable alloy strut tower brace	1	KSB504			KSB504	KSB504	
Options(4)	Front	Caster kit - VT series 1 only Caster kit fitting tool	1	KCA327 KCA327T	_		KCA327 KCA327T	KCA327 KCA327T	
		Swaybar link kit with bushes	1 1	KCA3271 KLC15			KCA3271 KLC15	KCA3271 KLC15	
		Heavy duty fixed swaybar - 30mm	1	BHF43			BHF43	BHF43	
		External adj. sport rated gas strut insert	2	D111 10	1301312	1301312	1301312	1301312	
	Rear	Extra h/duty fixed swaybar - 20mm	1	BHR50X			BHR50X	BHR50X	
		Blade adjustable swaybar - 20mm	1	BHR50Z			BHR50Z	BHR50Z	
		Adjustable sport rated gas shock	2		1101202	1101202	1101202	1101202	
		Spring spacer, LPG or extra load-12mm	1		SPF1358-5K	SPF1358-5K	SPF1358-5K	SPF1358-5K	

Suggested wheel alignment specs										
Optimum starting setting designed for use with Whiteline kit.		Camber(6)	Caster	Toe(6) mm/side						
Front	Touring	-1.5	L9.0 / R8.5	0.0						
	Sport	-2.0	L9.0 / R8.5	0.0						
Rear	Touring	-1.5	n/a	1.0 mm in						
	Sport	-2.0	n/a	0.5 mm in						

(1)-Height indicates measurement in mm from centre of wheel to guard, +/- 1.5%. Superlow applications with extra rear load can use standard low rear. These heights only available when using Whiteline specified shock absorbers.

(2)-Retail in A\$ includes GST, excl. freight. Special net price for package part number.

(3)-Sports and Works fitting prices include wheel alignment. Fitting and labour prices are meant as suggestions and are only available when purchasing parts kit from same dealer.

Handling Pack: Front swaybar replacement requires lowering of front cross member and removal of control arms and radius rods. Rear swaybar fitment best done after lowering front of rear cross member. Strut brace fitment requires some drilling.

Sports Pack: Shocks are straight foward replacement units but camber toe kit best fitted after lowering front of rear cross member.

(4)-Options: These items not included in package but available as separate item.

(5)-Front shocks are a twin tube gas sport rated replacement strut leg with special shortened body. Rear shocks are mono-tube gas sport rated type with shorter travel.

(6)-KCA330 kit replaces rear trailing arm bushes with eccentric adjusters. Includes 8 bushes and 4 tubes and all necessary fitting hardware. Suggested wheel alignment settings only available with KCA330 kit.